

2' x 2' L.E.D. Center Bevel (Retro-Fit)

Center mounted bevel channel houses advance optics to diffuse lamp image while providing superior even balanced illumination. Door hinge design for easy maintenance and washable surface. Supplied with Retro-Fit LED Luminaire, Brackets, Safety Cable and Relamping lables.

MOUNTING

Retro-Fit mounting into traditional 2x2 fluorescent Lay-In/Louver Troffers, specify (-RF).



2' x 4' L.E.D. Center Bevel (Retro-Fit)



2' x 4' L.E.D. Center Bevel



2' x 2' L.E.D. Center Bevel

MOUNTING

Suitable for standard exposed grid and screw slot T-bar ceilings, sheet rock or drywall ceiling. Optional for Recessed Flange Kit (FL) or Retro-Fit mounting into traditional 2x2 fluorescent Lay-In/Louver Troffers specify (RF). Reference Retro-Fit Spec Sheet for additional details.



DĀLUME®

Dynamic Architectural Lumination

2x2 & 2x4 Center-Bevel Retro-Fit Luminaire

2x2 & 2x4 High Output Center-Bevel

Lumen packages	Color Temp. CCT	Dim Options	Mounting	Price Point	Lumen packages	Color Temp. CCT	Dim Options	Mounting	Price Point
3085lm/ 25W	3000K	0-10V	2x2 Fluorescent Retro-Fit	\$\$	2780lm/ 27W	3000K	0-10V	2x2 New Installation	\$\$
4275lm/ 35W	3500K	Step Dimming*	2x4 Fluorescent Retro-Fit		4560lm/ 40W	3500K	Step Dimming*	2x2 New Installation	
	4000K				4335lm/ 40W	4000K		2x4 New Installation	
	5000K				7167lm/ 65W	5000K		2x4 New Installation	

Additional information including Specification Sheets, IES files and photos are available at dalume.com